


**EXTERIOR AND INTERIOR
PAINT COLOR SCHEDULE**
for
**PASSENGER and FREIGHT
STATIONS**
and
ROADWAY BUILDINGS

UNION PACIFIC RAILROAD COMPANY


EFFECTIVE JUNE, 1956

THE following exterior and interior paint colors are to be used for the painting of all passenger and freight stations and roadway buildings; with exception of such large passenger and freight stations and special designed small buildings which due to location and design would require a special paint specification. The painting of such buildings should be referred to the Chief Engineer for specifications.

EXTERIOR COLOR SCHEDULE



TITANIC OUTSIDE WHITE (1-54) UC-33710
Exterior of Entire Building



KENTUCKY GREEN (1-338) UC-33713
Trim on Window Sash Only

Buildings such as wash and locker rooms, yard offices, track motor car houses, garages and others where the lower portion of building is susceptible to discoloration due to its use shall have a painted wainscot using Kentucky Green — 1-338. The height of wainscot line from the grade line will be determined by the following:

Buildings so constructed as to have low exterior wainscots provided, its height shall be used for the dark color. Buildings not having an exterior wainscot shall be painted the darker color to the height of the window sills provided they are not above four feet (4') high. Should the building have all high windows or no windows, the dark wainscot should be to a line four feet (4') high around the building.

Brick or stone buildings having painted trim, such as windows and frames, doors and frames, cornice, gutters and downspouts etc. shall be trimmed using Titanic Outside White — 1-54.

Building constructed of exposed concrete block, poured concrete or stucco finish shall be painted with white masonry paint Cementhide 7-1.

Should it be necessary to use a colored masonry paint use Cementhide Tinting White 7-10 as the base and mix with the required Fluid Oil Colors in accordance with manufacturers directions to obtain the desired color.

ROOFS

Buildings constructed with wood shingle, asphalt shingle or metal roofs which require a dressing shall receive one coat of Green Roof-Dres as manufactured by Forman, Ford and Company, Minneapolis, Minn. and applied in accordance with manufacturers printed specifications.

INTERIOR COLOR SCHEDULE

Four interior paint color schedules are listed below. These colors are to be used in station buildings and living quarters and the color selection for various rooms shall be made by the Engineer in charge, Station Agent or other occupants and subject to approval of those in charge.

SCHEDULE A—Walls—Sun Tone—PBX Flat—24-211. Ceiling—White—PBX Flat—24-6. For matching wood trim and walls of bathrooms, kitchens or toilet rooms use Satinhide Sunny Yellow 60-112.

SCHEDULE A



SUNTONE (24-211) UC-33690



WHITE (24-6) UC-35350



SUNNY YELLOW (60-112) UC-34601

SCHEDULE B



SEAFOAM GREEN (24-116) UC-33679



WHITE (24-6) UC-35350



SEAFOAM GREEN (60-116) UC-34604

SCHEDULE B—Walls—Seafoam Green—PBX Flat—24-116. Ceiling—White—PBX Flat—24-6. For matching wood trim and walls of bathrooms, kitchens or toilet rooms use Satinhide Seafoam Green 60-116.

SCHEDULE C—Walls—Blossom Pink—PBX Flat—24-123. Ceiling—White—PBX Flat—24-6. For matching wood trim and walls of bathrooms, kitchens or toilet rooms use Satinhide Blossom Pink 60-123.

SCHEDULE D—Walls—Como Blue—PBX Flat—24-124. Ceiling—White—PBX Flat—24-6. For matching wood trim and walls of bathrooms, kitchens or toilet rooms use Satinhide Como Blue 60-124.

SCHEDULE C



BLOSSOM PINK (24-123) UC-33688



WHITE (24-6) UC-35350



BLOSSOM PINK (60-123) UC-34609

SCHEDULE D



COMO BLUE (24-124) UC-33689



WHITE (24-6) UC-35350



COMO BLUE (60-124) UC-34610

GENERAL

Buildings having stained and varnished woodwork, wainscoting, seats, counters and tops which are in good condition; these items shall be cleaned, sanded and refinished with clear dull varnish.

Buildings having stained and varnished floors which are in good condition; these floors shall be cleaned, sanded and refinished with clear gloss varnish.

Buildings having wood or concrete floors that require painting use FLORHIDE ENAMEL — Dixie Gray 3-17.

Buildings having clay tile floors and wainscoting or composition tile floors; these areas shall be thoroughly cleaned and waxed.



DIXIE GRAY (3-17) UC-33649

Buildings where radiators are installed for heating; these radiators shall be painted to conform with color of walls to which attached or placed.

SCHEDULE E


Freight, Baggage or Express Rooms, Warm and Hold Over Rooms.

Wainscot six feet (6') high shelving and woodwork—House Paint Pearl Gray—1-88.

Walls above wainscot and ceiling — House Paint — Titanic Outside White — 1-54.



PEARL GRAY (1-88) UC-33706



TITANIC OUTSIDE WHITE (1-54) UC-33710

INTERIOR EXPOSED WOOD OR PLYWOOD WALLS, CEILINGS AND PARTITIONS

All interior wood or plywood shall have a fire retardant coating of Bar-Flame Fibrekote No. 101 as manufactured by Barnard Chemical Co., 2405 W. Fourth St., Los Angeles, Calif., applied in strict accordance with manufacturer's printed specifications. This material to be used in their colors similar to Schedules A, B, C and D.