

5400 H.P. DIESEL FREIGHT LOCOMOTIVE . DESIGNED AND BUILT BY ELECTRO-MOTIVE DIVISION . GENERAL MOTORS CORPORATION . LA GRANGE ILLINOIS. U. S. A.

5400 H.P. DIESEL FREIGHT LOCOMOTIVE

Designed and Built For

ATLANTIC COAST LINE RAILROAD

BY ELECTRO-MOTIVE DIVISION ● GENERAL MOTORS CORPORATION ● LA GRANGE, ILLINOIS

This Diesel Freight Locomotive consists of two cab sections and two booster sections arranged for double end control from either cab, each being equipped with one General Motors, sixteen cylinder, V-type, 2 cycle Diesel engine having a bore of 8½", stroke 10" with unit injection system, rated at 1350 H.P. at 800 R.P.M., and developing a total of 5400 H.P. Each engine is direct connected to a D.C. generator, the

current of which is distributed to the traction motors mounted on the trucks which in turn are geared to the axles. There are a total of eight 4-wheel trucks under the four sections comprising this locomotive, each being equipped with two traction motors or a total of sixteen motors geared for a maximum speed of 80 M.P.H. All four engines are arranged for multiple control from either of the operator's cabs.

SPECIFICATIONS

DIMENSIONS

SUPPLIES

	-	_			-	
Fuel oil						4800 gals.
Sand						. 76 cu. ft.
Lubricating oil	(145)	gals	. per	engine)	.580 gals.
Engine cooling	water	(2	25 gal	is. per	engine)	. 900 gals.

WFIGHTS

11 2 1 0 11 1 3
Total weight fully loaded
Weight of locomotive with one-half of
variable supplies
Maximum tractive effort at rim of driving
wheels at 25% adhesion221,200 lbs

