

5400 H.P. DIESEL FREIGHT LOCOMOTIVE . . DESIGNED AND BUILT BY ELECTRO-MOTIVE DIVISION . . GENERAL MOTORS CORPORATION . . LA GRANGE, ILLINOIS, U. S. A.

5400 H.P. DIESEL FREIGHT LOCOMOTIVE

Designed and Built For

MISSOURI PACIFIC RAILROAD COMPANY

BY ELECTRO-MOTIVE DIVISION . GENERAL MOTORS CORPORATION . LA GRANGE, ILLINOIS

This Diesel Freight Locomotive consists of two cab sections and two booster sections arranged for double end control from either cab, each being equipped with one General Motors, sixteen cylinder, V-type, 2 cycle Diesel engine having a bore of 8½", stroke 10" with unit injection system, rated at 1350 H.P. at 800 R.P.M., and developing a total of 5400 H.P. Each engine is direct connected to a D.C. generator, the

current of which is distributed to the traction motors mounted on the trucks which in turn are geared to the axles. There are a total of eight 4-wheel trucks under the four sections comprising this locomotive, each being equipped with two traction motors or a total of sixteen motors geared for a maximum speed of 65 M.P.H. All four engines are arranged for multiple control from either of the operator's cabs.

SPECIFICATION

DIMENSIONS

Overall length over couplers
Maximum width over grab irons
Wigth over body posts9'-10"
Height over all, above rails
Wheel diameter40"
Rigid wheel base of trucks9'-0"
Roller bearing journals
Truck swing designed for 21° curve or 274-foot radius
Distance between truck centers on cab section 27'-3"
Distance between truck centers on booster section 26'-6"

SUPPLIES

			4800 gals
Lubricating oil	(145 gals.)	per engine)	
Engine cooling	water (225	gals. per eng	ine) 900 gals

WEIGHTS

Total weight fully loaded	Olbs.
Weight of locomotive with one-half of variable supplies	O Ibs.
Maximum tractive effort at rim of driving wheels at 25% adhesion	0 lbs.

